

# AGRIMAX V-FLECTO - Technical Specifications



## Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

## UM

US Standard

## Construction

 RADIAL

## Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 710/60 R 34 NRO
LI/SS	173 D

## Dimensions US Standard

Usa code	94069507
Section Width (inch)	27.9
Overall Diameter (inch)	67.6
Static Loaded Radius (inch)	29.6
Rolling Circumference (inch)	200.7
Rim Rec	DW 25 B
Rim Alt	DW 24 B ; DW 27 B
Narrow Rim option	DW 23 B
ECE	E11-106R-007201
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29
45	6660	7690	8740	9920	10820	11740	13040
From 40 to 25	7310	8450	9600	10890	11890	12900	14330
20	7460	8630	9800	11110	12140	13160	14620
12	7610	8800	9990	11330	12380	13410	14900
5	8050	9300	10570	11980	13080	14190	15760
*Upto 5 Cyc with front loader	10240	11840	13450	15260	16650	18050	20060
5 HT	7460	8630	9800	11110	12140	13160	14620

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 19/05/2024 11:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..