



AT 625 - Data Sheet



Description

AT 625 is suitable for backhoe loaders and compact loaders in all farming digging and loading operations. Its extra deep tread ensures increased puncture resistance and durability. AT 625 features excellent traction and stability as well as improved cut and chip resistance.

UM

US Standard

Construction

 BIAS

Machinery

Industrial: Backhoe Loader • Compact Loader

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
14.9 - 24	STANDARD	94051007	R4	145 A8	12	DW 13	DW 11 ; DW 12 ; DW 13 L	15.7	49.8	22.6	149.6	TL
14.9 - 24	STANDARD	94041367	R4	145 A8	12	DW 13	DW 11 ; DW 12 ; DW 13 L	15.7	49.8	22.6	149.6	TT
16.9 - 28	INDUSTRIAL	94051076	R4	152 A8	12	DW 15 L	DW 14 L	17.7	55.7	25.4	167.5	TL
16.9 - 28	INDUSTRIAL	94040315	R4	152 A8	12	DW 15 L	DW 14 L	17.7	55.7	25.4	167.5	TT
16.9 - 28	SPECIAL	94055470	R4	152 A8	12	DW 15 L	DW 14 L	17.7	55.7	25.4	167.5	TT

Printed on 19/05/2024 12:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..