

MULTIMAX MP 522 - Data Sheet



Description

MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Compact Loader • Telehandler

Industrial: Compact Loader • Telehandler

SIZE	Version	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
280/80 R 18 IND (10.5/80 R 18)	STANDARD	132 A8/B	W 9 ; 9 ; 9 SDC	W 8 ; W 10	282	907	421	2748	425	TL	E11-106R-002962
340/80 R 18 IND (12.5/80 R 18)	STANDARD	143 A8/B	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	343	1006	458	3023	475	TL	E4-106R-002654
340/80 R 20 IND	STANDARD	144 A8/B	11	W10 ; 11 SDC ; W11 ; 12 ; 12 SDC	343	1052	481	3212	500	TL	E11-106R-002969
380/75 R 20 IND (14.5 R 20)	STANDARD	148 A8/B	W 12	W 11 ; 11 ; 12	384	1074	483	3251	500	TL	E11-106R-002963
400/70 R 20 IND (16.0/70 R 20)	STANDARD	149 A8/B	13	12 SDC ; 13 SDC ; 14	404	1068	476	3199	525	TL	E4-106R-002319
400/70 R 24 IND	STANDARD	152 A8/B	13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	404	1170	533	3527	575	TL	E11-106R-002964
400/80 R 24 IND (16.0/80 R 24)	STANDARD	162 A8/B	DW 13	DW 12 ; DW 13 L ; DW 14 L	404	1250	553	3778	600	TL	E11-106R-002965
440/80 R 24 IND	STANDARD	161 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	441	1314	586	3958	625	TL	E11-106R-002966
460/70 R 24 IND (17.5L R 24)	STANDARD	159 A8/B	DW 15 L	DW 14 L ; DW 16 L	465	1250	568	3766	600	TL	E4-106R-002396
500/70 R 24 IND (19.5L R 24)	STANDARD	164 A8/B	DW 16 L	DW 15 L ; DW 18 L	503	1310	595	3940	625	TL	E4-106R-002395
540/70 R 24 IND	STANDARD	168 A8/B	DW 16 L	DW 18 L	530	1366	611	4133	650	TL	E11-106R-002967
480/80 R 26 IND	STANDARD	160 A8/B	DW 15 L	DW 16 L	479	1428	638	4287	675	TL	E11-106R-002970
480/80 R 26 IND	STANDARD	167 A8/B	DW 15 L	DW 16 L	479	1428	638	4287	675	TL	E11-106R-008146
440/80 R 28 IND	STANDARD	156 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	441	1415	643	4278	675	TL	E11-106R-002968

Printed on 19/05/2024 12:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..