

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	HD
Type	TL
Tyre Size	650/55 R 26.5
LI/SS	178 D

Dimensions International Standard

Section Width (mm)	645
Overall Diameter (mm)	1389
Static Loaded Radius (mm)	615
Rolling Circumference (mm)	4250
SRI (mm)	650
Rim Rec	AG 20.00
ECE	E11-106R-003008

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
65	2325	2775	3375	3900	4500	5100	5475	6075	6675	7050	7500
50	2815	3360	4085	4720	5445	6175	6625	7355	8080	8535	9075
40	3165	3775	4590	5305	6120	6940	7450	8265	9080	9590	10200
30	3515	4195	5100	5890	6795	7705	8270	9175	10080	10650	11325
25	3675	4385	5335	6165	7110	8060	8655	9600	10550	11140	11850
10	4185	4995	6075	7020	8100	9180	9855	10935	12015	12690	13500

Printed on 19/05/2024 09:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..