

RIDEMAX FL 693 M - Technical Specifications



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings. The low rolling resistance contributes to less fuel consumption, while a reinforced bead and steel belts ensure enhanced durability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tanker • Trailer

Version	HD
Type	TL
Tyre Size	710/50 R 26.5
LI/SS	179 D

Dimensions International Standard

Section Width (mm)	727
Overall Diameter (mm)	1383
Static Loaded Radius (mm)	606
Rolling Circumference (mm)	4217
SRI (mm)	650
Rim Rec	AG 24.00
Rim Alt	AG 20.00
ECE	E11-106R-006008

Load capacity (Kg)

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
70	1765	2260	2825	3175	3670	4165	4590	5010	5505	6210	7055
65	1940	2480	3100	3490	4030	4575	5040	5505	6045	6820	7750
50	2345	3005	3755	4225	4880	5535	6100	6660	7320	8255	9380
40	2635	3375	4220	4745	5485	6220	6855	7485	8225	9280	10540
30	2930	3750	4685	5270	6090	6910	7610	8315	9130	10305	11705
25	3065	3920	4900	5515	6370	7225	7960	8695	9555	10780	12245
10	3490	4465	5580	6280	7255	8235	9070	9905	10885	12280	13950

Printed on 19/05/2024 07:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..