

AT 621 - Specifiche tecniche



Description

AT 621 è idoneo per terne e pale compatte in tutte le operazioni di scavo e carico in ambito agricolo. Il battistrada dell'AT 621 è extra profondo per assicurare eccezionale resistenza a tagli e lacerazioni nonché maggiore durabilità. Inoltre, questo pneumatico BKT assicura ottime proprietà di autopulitura. AT 621 è disponibile in svariate versioni per rispondere alle esigenze più diverse degli utilizzatori.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Pala compatta • Terna
Industriale: Terna • Pala caricatrice

Version	INDUSTRIAL
Type	TT
Tyre Size	9.00 - 16
LI/SS	137 A6

Dimensions US Standard

Usa code	94051595
Ply Rating	16
Section Width (inch)	10.2
Overall Diameter (inch)	36.4
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-005364

Load capacity (lbs)

mph / psi	105
20	5070

Printed on 19/05/2024 09:52

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..