

## AT 625 - Specifiche tecniche



### Description

AT 625 è idoneo per terne e pale compatte in tutte le operazioni di scavo e carico in ambito agricolo. Il battistrada extra profondo garantisce un'incrementata resistenza alla perforazione e maggiore durabilità. AT 625 offre trazione e stabilità eccellenti nonché una migliore resistenza a tagli e strappi.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industriale: Terna • Pala compatta

Version	STANDARD
Type	TL
Tyre Size	14.9 - 24
LI/SS	145 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	400
Overall Diameter (mm)	1265
Static Loaded Radius (mm)	575
Rolling Circumference (mm)	3800
Rim Rec	DW 13
Rim Alt	DW 11 ; DW 12 ; DW 13 L
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.90
40	2900

Printed on 19/05/2024 17:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..