

## EARTHMAX SR 31 - Specifiche tecniche



### Description

EARTHMAX SR 31 è uno pneumatico radiale All Steel progettato per dumper rigidi e pale gommate. Le cinture in acciaio multistrato assicurano forza e stabilità straordinarie, mentre il disegno non-direzionale rigido a blocchi garantisce trazione e manovrabilità eccellenti, anche su fondo fangoso. Oltre allo straordinario comfort di guida, EARTHMAX SR 31 si distingue anche per una miscela speciale del battistrada, particolarmente resistente ai tagli e al calore. La struttura radiale della carcassa offre inoltre una bassa resistenza al rotolamento con conseguenti risparmi significativi di carburante.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Industriale: Dozer • Pala caricatrice

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	29.5 R 25
LI/SS	200 B/208 A2

## Dimensions US Standard

Usa code	94053742
TMPH	185
Overall Width (inch)	30.1
Overall Diameter (inch)	73.3
Static Loaded Radius (inch)	32.2
Rolling Circumference (inch)	218.7
Rim Rec	25.00/3.5
Star Rating	**/*
TRA Code	E3/L3

## Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	25400	26000	27600	28300	30000	30900
5	34200	35300	37500	38600	39700	-

Printed on 20/05/2024 03:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..