

## EARTHMAX SR 35 - Specifiche tecniche



### Description

Earthmax SR 35 è uno pneumatico radiale All Steel a basso profilo specificamente progettato per dumper articolati e pale gommate. È ideale per operazioni che richiedono eccellente trazione e galleggiamento. Earthmax SR 35 assicura sia trazione che stabilità eccellenti. Grazie alla robusta carcassa con cinture in acciaio, lo pneumatico garantisce straordinaria durabilità oltre a resistenza contro strappi e forature.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Dumper articolato • Dozer • Pala caricatrice

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	650/65 R 25 (25/65 R 25)
LI/SS	193 A2

## Dimensions International Standard

Overall Width (mm)	635
Overall Diameter (mm)	1498
Static Loaded Radius (mm)	669
Rolling Circumference (mm)	4493
Rim Rec	19.50/2.5
Star Rating	*
TRA Code	L3

## Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75
10	10000	10600	10900	11500

Printed on 19/05/2024 04:45

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..