

## EARTHMAX SR 49 M - Scheda tecnica



### Description

EARTHMAX SR 49 M è uno pneumatico All Steel con un particolare disegno non direzionale sviluppato per pale LHD, dumper di basso profilo (LPDT), pale gommate e dozer. che operano in condizioni severe in ambienti rocciosi, principalmente nelle miniere sotterranee. EARTHMAX SR 49 M è ideale per operazioni dure che richiedono trazione e stabilità eccezionali. Il battistrada di profondità L-4 e la miscela con formula speciale UMS (underground mine service) assicurano una maggiore resistenza all'usura del battistrada nonché eccellente resistenza contro tagli di roccia e forature.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Dozer • Pala LHD • Pala caricatrice • Dumper di basso profilo

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
26.5 R 25	CUT RESISTANT COMPOUND	94058976	L4	**	209 A2	22.00/3.0		27.9	70.2	31.5	208.5	TL	0
26.5 R 25	CUT RESISTANT COMPOUND	94058983	E4/L4	**/*	193 B/202 A2	22.00/3.0		27.9	70.2	31.5	208.5	TL	113
26.5 R 25	CUT RESISTANT COMPOUND	94058969	L4	*	202 A2	22.00/3.0		27.9	70.2	31.5	208.5	TL	0
26.5 R 25	CUT RESISTANT COMPOUND	94067930	E4/L4	****/****		22.00/3.0		27.9	70.2	31.5	208.5	TL	0
26.5 R 25	CUT RESISTANT COMPOUND (UMS)	94058990	E4	****		22.00/3.0		27.9	70.2	31.5	208.5	TL	0
29.5 R 25	CUT RESISTANT COMPOUND	94058457	L4	*	208 A2	25.00/3.5		30.7	75	33.2	220.5	TL	0
29.5 R 25	CUT RESISTANT COMPOUND	94058440	L4	**	216 A2	25.00/3.5		30.7	75	33.2	220.5	TL	0
29.5 R 25	CUT RESISTANT COMPOUND	94058426	E4/L4	**/*	200 B/208 A2	25.00/3.5		30.7	75	33.2	220.5	TL	151
29.5 R 25	CUT RESISTANT COMPOUND	94067947	E4/L4	****/****		25.00/3.5		30.7	75	33.2	220.5	TL	0
29.5 R 25	CUT RESISTANT COMPOUND (UMS)	94058433	E4	****		25.00/3.5		30.7	75	33.2	220.5	TL	0
29.5 R 29	CUT RESISTANT COMPOUND	94052400	L4	***	223 A2	25.00/3.5	24.00/3.5,26.00/3.5	30.9	79	35.7	248.8	TL	0
29.5 R 29	CUT RESISTANT COMPOUND (UMS)	94058648	E4	****		25.00/3.5	24.00/3.5, 26.00/3.5	30.9	79	35.7	248.8	TL	0

Printed on 19/05/2024 06:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..