

FL 695 - Specifiche tecniche



Description

FL 695 è stato appositamente progettato per i rimorchi in attività edilizie e di trasporto **agricolo** con un esclusivo profilo del battistrada con un blocco centrale. Grazie alla sua robusta carcassa, FL 695 può trasportare carichi pesanti mantenendo la stabilità in tutte le condizioni e il suo battistrada profondo assicura un'ottima autopulizia durante l'uso su strada e fuori strada. La presenza di strati multipli di corde d'acciaio rinforza questo modello contro le forature.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Rimorchio

Industriale: Rimorchio

| | |
|--------------------|---------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | 600/60 R 30.5 |
| LI/SS | 179 D |
| LI/SS DRIVE WHEEL | 179 D |
| LI/SS FREE ROLLING | 179 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94073832 |
| Section Width (inch) | 24.1 |
| Overall Diameter (inch) | 58.9 |
| Static Loaded Radius (inch) | 27.3 |
| Rolling Circumference (inch) | 180.6 |
| Rim Rec | AG20.00 |
| ECE | E11-106R-008503 |

Load capacity (lbs)

| mph / psi | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 65 | 73 | 80 | 87 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40 | -- | -- | -- | 7690 | 8880 | 10090 | 11110 | 12140 | 13330 | 14190 | 15030 | 16060 | 17080 |
| 30 | -- | -- | -- | 9310 | 10760 | 12200 | 13450 | 14680 | 16140 | 17170 | 18200 | 19440 | 20680 |
| 25 | -- | 7670 | 9530 | 10460 | 12090 | 13710 | 15110 | 16500 | 18130 | 19290 | 2060 | 21850 | 23240 |
| 20 | 6460 | 8520 | 10580 | 11620 | 13430 | 15230 | 16780 | 18330 | 20130 | 21430 | 22720 | 24260 | 25800 |
| 15 | 6760 | 8920 | 11080 | 12160 | 14040 | 15930 | 17550 | 19170 | 21060 | 22410 | 23760 | 25380 | 26990 |
| 10 | 7050 | 9310 | 11560 | 12700 | 14670 | 16640 | 18330 | 20030 | 22000 | 23410 | 24820 | 26510 | 28200 |
| 5 | 7690 | 10150 | 12610 | 13840 | 15990 | 17280 | 18150 | 19990 | 21840 | 24000 | 27070 | 28910 | 30750 |

Printed on 19/05/2024 17:32

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..