

MULTIMAX MP 527 - Scheda tecnica



Description

MULTIMAX MP 527 è un pneumatico radiale polivalente sviluppato per sollevatori telescopici e pale compatte nelle applicazioni agro-industriali. Lo pneumatico è dotato di un disegno a blocchi del battistrada che garantisce eccellente trazione anche sulle superfici più dure. Il fianco robusto dello pneumatico assicura straordinaria stabilità in modalità di sollevamento. MULTIMAX MP 527 è realizzato con una mescola particolarmente resistente a tagli e lacerazioni che si traduce in una lunga vita operativa dello pneumatico.

UM

International Standard

Construction

 RADIAL

Machinery

Agricoltura: Pala compatta • Sollevatore telescopico
Industriale: Pala compatta • Sollevatore telescopico

| SIZE | Version | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|---------------------------------------|----------|----------|------------------|--|-----|------|-----|------|-----|------|-----------------|
| 340/80 R 18 IND | STANDARD | 143 A8/B | 11; 11 SDC; W 11 | W 10; 12; 12 SDC | 343 | 1001 | 455 | 3028 | 475 | TL | E4-106R-002981 |
| 360/70 R 18 IND | STANDARD | 142 A8/B | 11 | W10; 11 SDC; W11; 12; 12 SDC | 360 | 969 | 439 | 2887 | 475 | TL | E11-106R-002996 |
| 340/80 R 20 IND | STANDARD | 144 A8/B | 11 | W10; 11 SDC; W11; 12; 12 SDC | 343 | 1052 | 483 | 3176 | 500 | TL | E11-106R-003957 |
| 400/70 R 20 IND (16.0/70 R 20) | STANDARD | 149 A8/B | 13 | 12 SDC; 13 SDC; 14 | 404 | 1068 | 494 | 3282 | 525 | TL | E4-106R-002656 |
| 400/70 R 24 IND | STANDARD | 152 A8/B | 13 | DW 12; DW 13; DW 13 L; 13 SDC; DW 14 L | 404 | 1170 | 542 | 3597 | 575 | TL | E11-106R-003958 |
| 400/80 R 24 IND | STANDARD | 162 A8/B | DW 13 | DW 12; DW 13 L; DW 14 L | 404 | 1250 | 578 | 3834 | 600 | TL | E11-106R-002982 |
| 440/80 R 24 IND | STANDARD | 161 A8/B | DW 14 L | DW 13; DW 13 L; DW 15 L | 441 | 1314 | 601 | 3985 | 625 | TL | E4-106R-002657 |
| 460/70 R 24 IND (17.5L R 24) | STANDARD | 159 A8/B | DW 15 L | DW 14 L; DW 16 L | 465 | 1254 | 574 | 3801 | 600 | TL | E11-106R-002983 |
| 500/70 R 24 IND | STANDARD | 164 A8/B | DW 16 L | DW 15 L; DW 18 L | 503 | 1310 | 597 | 4019 | 625 | TL | E4-106R-002658 |
| 480/80 R 26 IND | STANDARD | 160 A8/B | DW 15 L | DW 16 L | 479 | 1428 | 642 | 4259 | 675 | TL | E11-106R-004069 |
| 440/80 R 28 IND | STANDARD | 156 A8/B | DW 14 L | DW 13; DW 13 L; DW 15 L | 441 | 1415 | 648 | 4270 | 675 | TL | E11-106R-002984 |

Printed on 19/05/2024 16:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..