

RIDEMAX FL 693 M - Specifiche tecniche



Description

RIDEMAX FL 693 M è lo pneumatico ideale per chi deve percorrere frequentemente tratti stradali con rimorchi/autobotti. Sviluppato per un utilizzo del 75% su strada, RIDEMAX FL 693 M mostra delle prestazioni eccellenti su strada, dando la priorità al comfort e alle proprietà di autopulitura. L'indice di velocità classe D/E della gamma è sinonimo di velocità più elevate sui percorsi stradali con significativo risparmio di tempo. La bassa resistenza al rotolamento contribuisce ad un consumo minore di carburante, mentre il tallone rinforzato e le cinture in acciaio garantiscono una durabilità superiore.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Autobotte • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	710/45 R 22.5
LI/SS	165 D

Dimensions US Standard

Usa code	94062447
Section Width (inch)	27.8
Overall Diameter (inch)	47.7
Static Loaded Radius (inch)	21.3
Rolling Circumference (inch)	144
Rim Rec	AG 24.00
ECE	E11-106R-005994

Load capacity (lbs)

mph / psi	15	17	23	29	35	41	46	52	58
45	3780	4240	5270	6000	6920	7860	8580	9400	10330
40	4140	4660	5800	6590	7620	8630	9420	10340	11350
30	5030	5640	7010	7980	9210	10450	11420	12510	13750
25	5640	6340	7880	8960	10350	11740	12820	14050	15440
20	6260	7030	8750	9950	11500	13040	14240	15610	17150
15	6560	7360	9160	10420	12030	13650	14900	16340	17940
5	7460	8390	10430	11860	13700	15540	16960	18610	20440

Printed on 19/05/2024 12:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..