

## RT 747 AGRO INDUSTRIAL - Specifiche tecniche



### Description

RT 747 AGRO INDUSTRIAL è uno pneumatico radiale agro-industriale idoneo per pale compatte e sollevatori telescopici. I ramponi extra larghi assicurano eccellente trazione e straordinaria stabilità nelle operazioni di sollevamento. È stato progettato con una speciale miscela resistente a tagli e lacerazioni che consente allo pneumatico di trasportare carichi pesanti. RT 747 AGRO INDUSTRIAL è la giusta risposta per tutte le operazioni agricole che in generale richiedono una versatilità eccezionale.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Pala compatta • Sollevatore telescopico  
Industriale: Pala compatta • Sollevatore telescopico

|           |                             |
|-----------|-----------------------------|
| Version   | STANDARD                    |
| Type      | TL                          |
| Tyre Size | 500/70 R 24<br>(19.5L R 24) |
| LI/SS     | 157 A8/154 B                |

## Dimensions US Standard

|                              |                   |
|------------------------------|-------------------|
| Usa code                     | 94016822          |
| Section Width (inch)         | 19.1              |
| Overall Diameter (inch)      | 52                |
| Static Loaded Radius (inch)  | 23                |
| Rolling Circumference (inch) | 155.5             |
| Rim Rec                      | DW 16 L           |
| Rim Alt                      | DW 15 L ; DW 18 L |
| ECE                          | E11-106R-002988   |
| TRA Code                     | R4                |

## Load capacity (lbs)

| mph / psi | 17   | 23    | 29    | 35    | 41    | 44    |
|-----------|------|-------|-------|-------|-------|-------|
| 30        | 3890 | 4790  | 5620  | 6540  | 7360  | 8270  |
| 25        | 4280 | 5280  | 6180  | 7190  | 8090  | 9090  |
| 20        | 4570 | 5640  | 6610  | 7690  | 8660  | 9730  |
| 15        | 4750 | 5850  | 6870  | 7980  | 8980  | 10100 |
| 5 Cyc     | 6420 | 7910  | 9280  | 10780 | 12150 | 13650 |
| Static    | 8980 | 11080 | 12980 | 15090 | 17000 | 19100 |

Printed on 19/05/2024 14:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..