

AGRIMAX FORCE - Especificações técnicas



Description

AGRIMAX FORCE, o produto de ponta da BKT, é um pneu radial devidamente projetado para aplicações de tratamento do terreno, de transporte e de colheita com tratores de elevada potência, garantindo máximas prestações e eficiência. Com a tecnologia IF, este pneu permite-lhe transportar cargas pesadas a pressões de enchimento inferiores em comparação com o pneu estandarte reduzindo a compactação do solo. AGRIMAX FORCE é dotado de talão reforçado e assegura uma tração maior, propriedades de autolimpeza e economia de combustível, bem como uma experiência de condução confortável.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Trator de alta potencia

Version	STANDARD
Type	TL
Tyre Size	IF 650/65 R 38 CFO
LI/SS	169 D

Dimensions US Standard

Usa code	94059225
Section Width (inch)	25.6
Overall Diameter (inch)	72
Static Loaded Radius (inch)	32.7
Rolling Circumference (inch)	216.9
Rim Rec	DW 23 B
ECE	E11-106R-005103
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	5460	6390	7320	8130	8950	9640	10800	11630
From 40 to 25	6010	7030	8050	8950	9840	10600	11880	12790
20	6240	7310	8370	9300	10230	11020	12360	13290
12	6480	7590	8690	9660	10630	11440	12830	13800
5	7630	8930	10220	11360	12500	13460	15090	16240
Upto 20 Cyc	7800	9140	10460	11630	12790	13780	15440	16620
Upto 10 Cyc	9300	10890	12470	13870	15260	16430	18410	19820
Upto 5 Cyc	10210	11950	13680	15210	16730	18020	20190	21740
10HT	6240	7310	8370	9300	10230	11020	12360	13290

Printed on 19/05/2024 16:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..