

AGRIMAX RT 600 - Especificações técnicas

Description

AGRIMAX RT 600 é o pneu apropriado para prados e aplicações para a colheita e o espalhamento. Graças à sua ampla área de contacto, AGRIMAX RT 600 garante uma distribuição de pressão otimizada no terreno reduzindo os danos nos prados e protegendo o solo. Graças à tecnologia com ombros arredondados e um número elevado de blocos, assegura ótima estabilidade e tração.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Espalhador • Trator



| | |
|-----------|--------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 650/65 R 38 |
| LI/SS | 157 D/160 A8 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 645 |
| Overall Diameter (mm) | 1811 |
| Static Loaded Radius (mm) | 833 |
| Rolling Circumference (mm) | 5443 |
| SRI (mm) | 875 |
| Rim Rec | DW 20 B |
| ECE | E11-106R-002990 |

Load capacity (Kg)

| km/h / bar | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 2310 | 2725 | 3095 | 3465 | 3795 | 4125 |
| 50 | 2430 | 2865 | 3255 | 3645 | 3990 | 4335 |
| 40 | 2520 | 2970 | 3375 | 3780 | 4140 | 4500 |
| 30 | 2660 | 3135 | 3560 | 3990 | 4370 | 4745 |
| 10 LT | 3100 | 3650 | 4150 | 4650 | 5090 | 5530 |
| 10 HT | 2660 | 3135 | 3560 | 3990 | 4370 | 4745 |

Printed on 19/05/2024 14:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..