

AGRIMAX RT 600 - Especificações técnicas

Description

AGRIMAX RT 600 é o pneu apropriado para prados e aplicações para a colheita e o espalhamento. Graças à sua ampla área de contacto, AGRIMAX RT 600 garante uma distribuição de pressão otimizada no terreno reduzindo os danos nos prados e protegendo o solo. Graças à tecnologia com ombros arredondados e um número elevado de blocos, assegura ótima estabilidade e tração.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Espalhador • Trator



Version	STANDARD
Type	TL
Tyre Size	750/65 R 26
LI/SS	171 A8/B

Dimensions International Standard

Section Width (mm)	750
Overall Diameter (mm)	1636
Static Loaded Radius (mm)	737
Rolling Circumference (mm)	4987
SRI (mm)	775
Rim Rec	DW 24 B
Rim Alt	DW 23 B ; DW 25 B
ECE	E11-106R-006182

Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	2830	3260	3690	4000	4370	4860	5230	5720	6150	-	-
40	2830	3260	3690	4000	4370	4860	5230	5720	6150	-	-
30	3030	3495	3955	4285	4680	5205	5600	6125	6585	-	-
10 LT	3795	4370	4950	5360	5855	6515	7010	7670	8245	-	-
10 HT	3030	3495	3955	4285	4680	5205	5600	6125	6585	-	-
10 Cyc	-	5240	5930	6425	7015	7810	8400	9190	9880	10010	10455

Printed on 19/05/2024 18:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..