

## AGRIMAX RT 600 - Especificações técnicas

### Description

AGRIMAX RT 600 é o pneu apropriado para prados e aplicações para a colheita e o espalhamento. Graças à sua ampla área de contacto, AGRIMAX RT 600 garante uma distribuição de pressão otimizada no terreno reduzindo os danos nos prados e protegendo o solo. Graças à tecnologia com ombros arredondados e um número elevado de blocos, assegura ótima estabilidade e tração.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Ceifeira • Espalhador • Trator



Version	STANDARD
Type	TL
Tyre Size	900/60 R 32
LI/SS	181 A8/178 B

## Dimensions US Standard

Usa code	94062423
Section Width (inch)	35.3
Overall Diameter (inch)	74.5
Static Loaded Radius (inch)	33.1
Rolling Circumference (inch)	224.3
Rim Rec	DW 27 B
Rim Alt	DW 28 B ; DW 30 B
ECE	E11-106R-005768

## Load capacity (lbs)

mph / psi	12	15	17	20	23	29	35	41	46	49	55
30	7440	8430	9590	10580	11740	13060	14050	15380	16530	-	-
25	8190	9280	10550	11640	12920	14370	15460	16920	18190	-	-
20	8760	9930	11300	12470	13820	15390	16560	18110	19470	-	-
5 LT	10970	12430	14140	15610	17310	19260	20720	22670	24370	-	-
5 HT	8760	9930	11300	12470	13820	15390	16560	18110	19470	-	-
5 Cyc.	-	14910	16950	18710	20760	23090	24840	27180	29220	29680	30920

Printed on 19/05/2024 11:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..