

## AGRIMAX V-FLECTO - Especificações técnicas



### Description

AGRIMAX V-FLECTO é a resposta BKT à exigência desafiante em termos de tecnologia e desempenho para tratores de elevada potência. O pneu é perfeito para aplicações de tratamento do terreno e de transporte graças à uma compactação reduzida e ótimas qualidades de autolimpeza. Com a tecnologia VF exclusiva, AGRIMAX V-FLECTO permite-lhe transportar cargas muito pesadas a pressões de enchimento inferiores em comparação com pneus standard e IF alcançando velocidades elevadas. É dotado de Narrow Rim Option (jante estreita) que permite montar jantes standard. BKT projetou este pneu com geometria otimizada para aumentar o conforto de condução no campo e na estrada reduzindo o consumo de combustível.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Trator de alta potencia

Version	STANDARD
Type	TL
Tyre Size	VF 650/60 R 42
LI/SS	174 D

## Dimensions US Standard

Usa code	94074808
Section Width (inch)	26
Overall Diameter (inch)	72.6
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	219.1
Rim Rec	DW 23 B
Rim Alt	DW21B
ECE	E11-106R-008774

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	6170	7120	8190	9130	10210	11140	12490	13440
From 40 to 25	6790	7830	9010	10040	11220	12260	13730	14770
20	6920	7970	9180	10230	11440	12490	14000	15060
12	7050	8130	9360	10440	11660	12740	14270	15350
5	7470	8610	9910	11040	12350	13480	15100	16250
*Upto 5 Cyc with front loader	9500	10960	12610	14050	15710	17160	19220	20680
5 HT	6920	7970	9180	10230	11440	12490	14000	15060

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 19/05/2024 11:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..