

EARTHMAX SR 313 - Dados técnicos



Description

O EARTHMAX SR 313 é um pneu radial integralmente em aço, desenhado para os camiões basculantes articulados e pás carregadoras a trabalhar em terrenos rochosos duros. Com o composto resistente aos cortes e design de piso especial, protege contra os cortes e danos e oferece propriedades de autolimpeza. O design quadrado maximiza o contacto com o solo, garantindo excelente manobrabilidade. A construção radial integralmente em aço com lonas de cima de várias camadas proporciona durabilidade adicional. O EARTHMAX SR 313 é o pneu ideal para transporte, bem como carga e transporte.

UM

US Standard

Construction

 RADIAL

Machinery

OTR: Dumper Articulado • Carregadora

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
15.5 R 25	CUT RESISTANT COMPOUND	94066964	E3/L3	**/*	160 B/169 A2	12.00/1.3		15.5	49.8	22.3	150.5	TL	92

Printed on 19/05/2024 17:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..