

EARTHMAX SR 41 - Especificações técnicas



Description

EARTHMAX SR 41 é um pneu radial All Steel perfeito para carregadoras e tratores de esteira nas aplicações de transporte, carga e nivelamento. Graças à sua estrutura All Steel e ao desenho caracterizado por blocos, EARTHMAX SR 41 proporciona uma resistência excelente aos furos e uma durabilidade prolongada. Além das muitas horas de trabalho sem ter de parar a máquina, o pneu assegura um conforto excepcional. EARTHMAX SR 41 (E-4/L-4) é um pneu radial All Steel ideal para dumper articulados, pás carregadoras e escavadoras.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Dumper Articulado • Trator de esteira • Carregadora
• Dumper de baixo perfil

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	23.5 R 25
LI/SS	185 B/195 A2

Dimensions International Standard

TKPH	161
Overall Width (mm)	615
Overall Diameter (mm)	1611
Static Loaded Radius (mm)	725
Rolling Circumference (mm)	4790
Rim Rec	19.50/2.5
Star Rating	**/*
TRA Code	E4/L4

Load capacity (Kg)

km/h / bar	4.00	4.25	4.50	4.75	5.00	5.25
50	7500	7750	8250	8500	9000	9250
10	10300	10600	11200	11500	12150	--

Printed on 19/05/2024 19:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..