

EARTHMAX SR 44 - Especificações técnicas



Description

EARTHMAX SR 44 é um pneu radial **All Steel** apropriado para uma série de aplicações, inclusive operações na mina, de transporte e na floresta. O desenho robusto do pneu do piso E-4 assegura uma tração e um conforto excelentes para o operador. EARTHMAX SR 44 (E-4) é capaz de otimizar a produtividade, seja qual for a sua operação.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Camião basculante

| | |
|-----------|------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 11.00 R 20 |

Dimensions International Standard

| | |
|----------------------------|--------------------|
| Overall Width (mm) | 282 |
| Overall Diameter (mm) | 1111 |
| Static Loaded Radius (mm) | 520 |
| Rolling Circumference (mm) | 3328 |
| Rim Rec | 8.00 |
| Rim Alt | 7.50 ; 8.50;8.50VM |
| Star Rating | *** |
| TRA Code | E4 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 7.75 |
| 50 | 3760 |

Printed on 19/05/2024 12:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..