

## FL 630 ULTRA - Especificações técnicas



### Description

FL 630 ULTRA é idóneo para aplicações com reboques, cisternas móveis e espalhadores. Gracias ao talão reforçado e o particular desenho do piso do pneu, o pneu é ideal para um uso polivalente em qualquer tipo de terreno o na estrada. FL 630 ULTRA é sinónimo de uma compactação do solo extraordinariamente reduzida.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Espalhador • Cisterna móvel • Reboque

Version	STANDARD
Type	TL
Tyre Size	600/50 R 22.5
LI/SS	159 D/170 A8

## Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1172
Static Loaded Radius (mm)	518
Rolling Circumference (mm)	3533
SRI (mm)	550
Rim Rec	AG 20.00
ECE	E11-106R-003960

## Load capacity (Kg)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1280	1480	1675	2020	2355	2680	3020	3330	3670	3985
65	1400	1620	1840	2220	2585	2950	3310	3660	4025	4375
50	1695	1960	2225	2700	3125	3575	4000	4420	4875	5295
40	1920	2220	2520	3040	3540	4050	4555	5020	5520	6000
25	2215	2560	2905	3510	4080	4675	5210	5800	6365	6915
10	2520	2915	3310	4000	4650	5325	5940	6600	7245	7875

Printed on 19/05/2024 04:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..