

## FL 630 ULTRA - Especificações técnicas



### Description

FL 630 ULTRA é idóneo para aplicações com reboques, cisternas móveis e espalhadores. Gracias ao talão reforçado e o particular desenho do piso do pneu, o pneu é ideal para um uso polivalente em qualquer tipo de terreno o na estrada. FL 630 ULTRA é sinónimo de uma compactação do solo extraordinariamente reduzida.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Espalhador • Cisterna móvel • Reboque

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 600/55 R 26.5 |
| LI/SS     | 165 D/176 A8  |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 611             |
| Overall Diameter (mm)      | 1333            |
| Static Loaded Radius (mm)  | 579             |
| Rolling Circumference (mm) | 4070            |
| SRI (mm)                   | 625             |
| Rim Rec                    | AG 20.00        |
| ECE                        | E11-106R-006813 |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 65         | 1650 | 1910 | 2165 | 2630 | 3040 | 3505 | 3970 | 4275 | 4740 | 5150 |
| 50         | 2000 | 2310 | 2620 | 3180 | 3680 | 4240 | 4805 | 5180 | 5740 | 6235 |
| 40         | 2275 | 2630 | 2985 | 3625 | 4190 | 4830 | 5470 | 5895 | 6535 | 7100 |
| 25         | 2605 | 3015 | 3420 | 4155 | 4805 | 5540 | 6270 | 6760 | 7490 | 8140 |
| 10         | 2970 | 3435 | 3895 | 4730 | 5470 | 6305 | 7140 | 7695 | 8530 | 9270 |

Printed on 19/05/2024 06:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..