

MULTIMAX MP 522 - Especificações técnicas



Description

MULTIMAX MP 522 é o pneu polivalente da BKT desenvolvido para ser utilizado em muitos campos no setor agroindustrial. É apropriado para todas as operações de elevação e carga em veículos tais como levantadores telescópicos e pás compactas. Estabilidade e tração são os pontos de força associados à resistência excepcional aos furos. Graças ao composto de borracha especial, MULTIMAX MP 522 fornece uma resistência extraordinária aos cortes e lacerações.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Carregadora compacta • Levantador telescópico

Industrial: Carregadora compacta • Levantador telescópico

Version	STANDARD
Type	TL
Tyre Size	400/70 R 20 IND (16.0/70 R 20)
LI/SS	149 A8/B

Dimensions US Standard

Usa code	94033829
Section Width (inch)	15.9
Overall Diameter (inch)	42
Static Loaded Radius (inch)	18.7
Rolling Circumference (inch)	125.9
Rim Rec	13
Rim Alt	12 SDC ; 13 SDC ; 14
ECE	E4-106R-002319

Load capacity (lbs)

mph / psi	23	29	35	41	46	51	58	61	64
30	3440	4090	4660	5300	5950	6380	7160	-	-
25	3440	4090	4660	5300	5950	6380	7160	-	-
20	3690	4380	4990	5690	6370	6830	7670	-	-
15	3820	4540	5180	5900	6610	7090	7960	-	-
5 Cyc	4200	5160	6070	6990	7960	8650	9790	10320	10750
Static	6440	7910	9310	10710	12200	13270	15000	15830	16480

Printed on 19/05/2024 16:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..