

RIDEMAX FL 693 M - Especificações técnicas



Description

RIDEMAX FL 693 M é o pneu ideal para quem tem de percorrer frequentemente troços rodoviários com reboques/cisternas móveis. Realizado para uma utilização de 75% na estrada, RIDEMAX FL 6936 M mostra prestações excelentes na estrada, dando a prioridade ao conforto e às propriedades de auto limpeza. O índice de velocidade classe D/E da gama é sinónimo de velocidades mais elevadas em percursos rodoviários com enorme poupança de tempo. A baixa resistência ao rolamento contribui para um consumo menor de combustível, enquanto o talão reforçado e os cintos de aço asseguram maior durabilidade.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Cisterna móvel • Reboque

Version	STANDARD
Type	TL
Tyre Size	560/60 R 22.5
LI/SS	169 D

Dimensions US Standard

Usa code	94066193
Section Width (inch)	21.4
Overall Diameter (inch)	49
Static Loaded Radius (inch)	21.7
Rolling Circumference (inch)	148.3
Rim Rec	AG 16.00
Rim Alt	16.00 ; 17.00 ; AG 20.00
ECE	E11-106R-006650

Load capacity (lbs)

mph / psi	17	23	29	35	41	46	52	58	73	87
45	3850	4770	5250	6060	6880	7570	8270	9080	10250	11640
40	4220	5250	5750	6660	7550	8310	9080	9980	11250	12790
30	5110	6350	6970	8060	9140	10060	10990	12080	13620	15480
25	5740	7130	7840	9050	10270	11310	12360	13570	15310	17390
15	6670	8290	9090	10520	11930	13140	14350	15760	17790	20200
5	7610	9450	10360	11970	13580	14970	16350	17960	20260	23010

Printed on 19/05/2024 05:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..