

RIDEMAX FL 693 M - Especificações técnicas



Description

RIDEMAX FL 693 M é o pneu ideal para quem tem de percorrer frequentemente troços rodoviários com reboques/cisternas móveis. Realizado para uma utilização de 75% na estrada, RIDEMAX FL 6936 M mostra prestações excelentes na estrada, dando a prioridade ao conforto e às propriedades de auto limpeza. O índice de velocidade classe D/E da gama é sinónimo de velocidades mais elevadas em percursos rodoviários com enorme poupança de tempo. A baixa resistência ao rolamento contribui para um consumo menor de combustível, enquanto o talão reforçado e os cintos de aço asseguram maior durabilidade.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Cisterna móvel • Reboque

Version	STANDARD
Type	TL
Tyre Size	650/50 R 22.5
LI/SS	168 D

Dimensions US Standard

Usa code	94055654
Section Width (inch)	25.4
Overall Diameter (inch)	48.1
Static Loaded Radius (inch)	21.1
Rolling Circumference (inch)	146.3
Rim Rec	AG 20.00
ECE	E11-106R-006489

Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	73
45	3260	4170	5060	5740	6640	7540	8320	9120	10010	11240
40	3580	4570	5560	6300	7290	8280	9140	10010	10990	12300
30	4340	5530	6790	7630	8830	10020	11070	12110	13300	14950
25	4870	6220	7640	8580	9920	11260	12430	13610	14960	16800
20	5410	6910	8480	9510	11010	12500	13810	15110	16600	18650
15	5670	7220	8860	9950	11520	13070	14440	15810	17370	19510
5	6450	8220	10100	11340	13120	14890	16450	18000	19790	22220

Printed on 19/05/2024 03:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..