

TR 387 IND - Especificações técnicas



Description

TR 387 IND é um pneu industrial, apropriado para reboques agrícolas e compactadores. O pneu destaca-se pela elevada capacidade de carga e está disponível em várias versões, com vista a atender às exigências específicas dos utilizadores em termos de resistência a cortes e rasgões, operações de serviço pesado e duração. A versão "dual bead", de talão duplo, é apropriada particularmente para tratores industriais e operações de transporte com reboques.

UM

International Standard

Construction

❖ BIAS

Machinery

Industrial: Compactador • Trator • Reboque

| | |
|-----------|--------------|
| Version | DUAL BEAD HD |
| Type | TL |
| Tyre Size | 24.5 - 32 |
| LI/SS | 164 A6 |

Dimensions International Standard

| | |
|----------------------------|------------------------------|
| Ply Rating | 16 |
| Section Width (mm) | 625 |
| Overall Diameter (mm) | 1755 |
| Static Loaded Radius (mm) | 790 |
| Rolling Circumference (mm) | 5226 |
| Rim Rec | DH 21 |
| Rim Alt | DH 21 B ; DH 21 H ; DH 21 HB |
| TRA Code | R3 |

Load capacity (Kg)

| | |
|------------|------|
| km/h / bar | 2.10 |
| 30 | 5000 |

Printed on 19/05/2024 10:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..