

TR 463 - Especificações técnicas



Description

TR 463 foi especialmente desenvolvido para retroescavadoras e tratores industriais. Realizado com um composto de borracha superior do piso do pneu, junto com uma carcaça robusta em nylon, o pneu garante os melhores resultados nas aplicações industriais e OTR, bem como nos estaleiros. TR 463 assegura uma tração excelente para as rodas motrizes.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Retroescavadora • Trator

Version	INDUSTRIAL
Type	TL
Tyre Size	16.9 - 24
LI/SS	149 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	445
Overall Diameter (mm)	1300
Static Loaded Radius (mm)	584
Rolling Circumference (mm)	3877
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.60
40	3250

Printed on 19/05/2024 18:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..