

AGRIMAX FORCE - Fișa de date



Descriere

AGRIMAX FORCE, produsul de ultimă generație al BKT, este o anvelopă radială special concepută pentru aplicații de cultivare a solului, transport și recoltare cu tractoare și combine de mare putere, asigurând performanță și eficiență de top. Datorită tehnologiei sale IF, această anvelopă poate suporta sarcini grele cu o presiune de umflare mai mică în comparație cu o anvelopă standard, reducând compactarea solului. AGRIMAX FORCE are un talon ranforsat și oferă tracțiune îmbunătățită, proprietăți de auto-curățare superioare și economie de combustibil, pe lângă experiența confortabilă la condus.

UM

US Standard

Construcție



RADIAL

Mașinării

Agricultură: Mașină de recoltare • Tractor de mare putere

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
IF 600/70 R 28	STANDARD	94044689	R1W	164 D	DW 21 B	DW 20 B	23.7	61.1	27.3	183.2	TL	E4-106R-000795
IF 710/55 R 28 CFO	STANDARD	94059690	R1W	165 D	DW 25 B		28.2	58.8	26.1	174.9	TL	E11-106R-005498
IF 600/70 R 30 CFO	SPECIAL	94060047	R1W	165 D	DW 21 B ; DW 21 A	DW 20 A ; DW 20 B	23.7	63.1	27.9	189	TL	E11-106R-006495
IF 600/70 R 30 CFO	STANDARD	94045211	R1W	165 D	DW 21 B ; DW 21 A	DW 20 A ; DW 20 B	23.7	63.1	27.9	189	TL	E11-106R-006495
IF 620/75 R 30 CFO	STANDARD	94064717	R1W	169 D	DW 23 B	DW 21 B	25.6	67	29.9	200.8	TL	E11-106R-006496
IF 710/60 R 30 CFO	STANDARD	94038541	R1W	168 D	DW 25 B		27.9	63.5	28.1	189.5	TL	E4-106R-001407
IF710/55 R 30 CFO	STANDARD	94059904	R1W	166 D	DW 25 B		28.2	60.8	27	181.7	TL	E11-106R-005716
IF 600/70 R 34	STANDARD	94045228	R1W	167 D	DW 21 B ; DW 21 A	DW 20 A ; DW 20 B	23.7	67.1	29.8	199.6	TL	E4-106R-001408
IF 650/60 R 34	STANDARD	94063628	R1W	165 D	DW 23 B	DW 21 B	25.6	64.7	29.4	195	TL	E11-106R-006014
IF 650/65 R 34 CFO	SPECIAL	94060054	R1W	161 D	DW 23 B	DW 20 B	25.6	67.3	30.1	199.9	TL	E4-106R-001826
IF 650/65 R 34 CFO	STANDARD	94040742	R1W	161 D	DW 23 B	DW 20 B	25.6	67.3	30.1	199.9	TL	E4-106R-001826
IF 710/55 R 34 CFO	STANDARD	94059942	R1W	170 D	DW 25 B		28.2	64.8	29.4	195.4	TL	E11-106R-005995
IF 710/60 R 34 CFO	SPECIAL	94060061	R1W	170 D	DW 25 B		27.9	67.6	30	201.8	TL	E4-106R-001485
IF 710/60 R 34 CFO	STANDARD	94022229	R1W	170 D	DW 25 B		27.9	67.6	30	201.8	TL	E4-106R-001485
IF 710/75 R 34 CFO	STANDARD	94053643	R1W	178 D	DW 25 B	DW 23 B	28.2	75.9	34.3	227.4	TL	E11-106R-003017
IF 380/80 R 38	STANDARD	94062140	R1W	149 D	W 12	W 11 ; W 13	15	61.9	28.5	188.7	TL	E11-106R-005715
IF 420/85 R 38	STANDARD	94058044	R1W	155 D	DW 14 L	DW 15 L	16.5	65.7	30.7	197.5	TL	E11-106R-004897
IF 650/65 R 38 CFO	STANDARD	94059225	R1W	169 D	DW 23 B		25.6	72	32.7	216.9	TL	E11-106R-005103
IF 650/75 R 38 CFO	STANDARD	94069477	R1W	175 D	DW 23 B	DW 21 B	25.6	76.4	34.1	228.4	TL	E11-106R-007385
IF 650/85 R 38 CFO	STANDARD	94051236	R1W	179 D	DW 23 B	DW 20 B ; DW 21 B	26.1	81.5	36.5	240.4	TL	E4-106R-002649
IF 710/60 R 38	STANDARD	94057511	R1W	172 D	DW 25 B		27.9	71.5	32	212.8	TL	E11-106R-004754
IF 800/70 R 38 CFO	STANDARD	94055784	R1W	184 D	DW 27 B	DW 25 B, DW 28 B, DW 30 B	31.3	82.1	36.3	243.5	TL	E11-106R-006497
IF 900/60 R 38 CFO	STANDARD	94038749	R1W	184 D	DW 30 A ; DW 30 B	TW 31 B	36.1	80.5	35.6	240.4	TL	E11-106R-006493
IF 650/85 R 42 CFO	STANDARD	94046904	R1W	180 D	DW 23 B		25.6	85.6	38	252	TL	E4-106R-001832
IF 710/70 R 42 CFO	SPECIAL	94060078	R1W	179 D	DW 25 B	DW 23 B	28.2	81.1	36.2	242.8	TL	E4-106R-001830
IF 710/70 R 42 CFO	STANDARD	94040926	R1W	179 D	DW 25 B	DW 23 B	28.2	81.1	36.2	242.8	TL	E4-106R-001830
IF 710/75 R 42 CFO	SPECIAL	94060085	R1W	181 D	DW 25 B	DW 23 B	28.2	84	38.1	252.1	TL	E11-106R-006490
IF 710/75 R 42 CFO	STANDARD	94046010	R1W	181 D	DW 25 B	DW 23 B	28.2	84	38.1	252.1	TL	E11-106R-006490
IF 800/70 R 42 CFO	STANDARD	94073658	R1W	192 D	DW 27 B	DW 25 B, DW 28 B, DW 30 B	31.3	84.6	37.4	252	TL	E11-106R-006481
IF 800/70 R 42	STANDARD	94073641	R1W	186	DW 27 B	DW 25 B, DW 28 B, DW	31.3	84.6	37.4	252	TL	E4-106R-

CFO				D	30 B				002650			
IF 900/50 R 42 CFO	STANDARD	94058471	R1W	180 D	DW 30 B	TW 30 B	34.7	77	34.3	229.5	TL	E11-106R-006492
IF 900/60 R 42 CFO	STANDARD	94022236	R1W	186 D	DW 30 B	TW 30 B	36.1	84.5	37.4	252.6	TL	E11-106R-006494
IF 750/75 R 46 CFO	STANDARD	94058082	R1W	186 D	DW 25 B		29.2	90.3	40.6	267.8	TL	E11-106R-006491
IF 480/95 R 50	STANDARD	94058006	R1W	170 D	DW 16 B		18.9	85.4	39.4	258.8	TL	E11-106R-004898

Imprimat pe 5/19/2024 3:16 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..