

AGRIMAX V-FLECTO - Fișa de date



Descriere

AGRIMAX V-FLECTO este răspunsul BKT la cererea de tehnologie și performanță pentru tractoare de mare putere. Această anvelopă este perfectă pentru aplicații de cultivare a solului și de transport datorită compactării reduse a solului și proprietăților de auto-curățare. Cu tehnologia exclusivă VF, AGRIMAX V-FLECTO poate transporta sarcini grele cu o presiune de umflare mai mică în comparație cu anvelopele standard și IF, atingând viteze mari. Dispune, de asemenea, de Narrow Rim Option (Opțiunea cu jante înguste) care permite montarea jantelor standard pe anvelopă. BKT a proiectat această anvelopă cu geometrie optimizată pentru a spori confortul la condus atât pe câmp, cât și pe drum, reducând consumul de combustibil.

UM

Standard internațional

Construcție

 RADIAL

Mașinării

Agricultură: Tractor de mare putere

SIZE	Version	TRA Code	LI/SS	RIM REC	RIM ALT	NRO	SW	OD	SLR	RC	SRI	Type	ECE
VF 480/60 R 28 NRO	STANDARD	R1W	145 D	DW 16 L	W 16 L	W 15 L	470	1290	571	3807	625	TL	E11-106R-005496
VF 520/60 R 28 NRO	STANDARD	R1W	149 D	DW 18 L	W 18 L	DW 16 L	516	1335	587	3910	650	TL	E11-106R-005497
VF 540/65 R 28 NRO	STANDARD	R1W	154 D	DW 20 B	DW 18 L	DW 16 L	549	1413	622	4160	675	TL	E11-106R-005710
VF 600/60 R 28 NRO	STANDARD	R1W	157 D	DW 20 B	DW 18 L	DW 18 L	587	1440	632	4228	675	TL	E11-106R-004471
VF 600/65 R 28 NRO	STANDARD	R1W	163 D	DW 21 B	DW 20 B	DW 18 L	597	1491	655	4453	700	TL	E11-106R-007602
VF 600/70 R 28	STANDARD	R1W	167 D	DW 21 B	DW 20 B		603	1551	662	4572	725	TL	E11-106R-008814
VF 540/65 R 30 NRO	STANDARD	R1W	158 D	DW 20 B	DW 18 L	DW 16 L	549	1464	650	4351	700	TL	E11-106R-005711
VF 600/60 R 30 NRO	STANDARD	R1W	158 D	DW 20 B	DW 18 L ; DW 21 B	DW 18 L	595	1485	649	4404	700	TL	E11-106R-002979
VF 600/70 R 30 NRO	STANDARD		168 D	DW 21 B	DW 20 B	DW 18 B	603	1602	702	4711	750	TL	E11-106R-006162
VF 600/60 R 34	STANDARD	R1W	160 D	DW 20 B	DW 18 L ; DW 21 B	DW 18 L	595	1584	691	4710	750	TL	E11-106R-008773
VF 600/65 R 34 NRO	STANDARD	R1W	169 D	DW 21 B	DW 20 B	DW 18 L	597	1644	731	4952	775	TL	E11-106R-007603
VF 600/70 R 34 NRO	STANDARD	R1W	170 D	DW 21 B	DW 20 B	DW 18 B	603	1704	740	5040	800	TL	E11-106R-008813
VF 650/60 R 34	STANDARD		168 D	DW 23 B	DW21B		660	1676	750	4996	775	TL	E11-106R-007210
VF 650/65 R 34 NRO	STANDARD	R1W	170 D	DW 23 B	DW 21 B	DW 20 B	650	1710	761	5153	825	TL	E11-106R-008812
VF 710/60 R 34 NRO	STANDARD	R1W	173 D	DW 25 B	DW 24 B ; DW 27 B	DW 23 B	708	1716	752	5097	825	TL	E11-106R-007201
VF 480/80 R 38	STANDARD	R1W	166 D	DW 16 L	DW 15 L		479	1733	774	5169	825	TL	E11-106R-007168
VF 540/65 R 38 NRO	STANDARD	R1W	162 D	DW 20 B	DW 18 L	DW 16 L	549	1676	760	4981	800	TL	E11-106R-005020
VF 600/60 R 38 NRO	STANDARD	R1W	168 D	DW 20 B	DW 18 L	DW 18 L	587	1685	757	5077	800	TL	E11-106R-006414
VF 600/60 R 38 NRO	STANDARD	R1W	166 D	DW 20 B	DW 18 L	DW 18 L	587	1685	757	5081	800	TL	E11-106R-005021
VF 650/60 R 38 NRO	STANDARD	R1W	173 D	DW 23 B	DW 21 B	DW 20 B	650	1745	774	5217	825	TL	E11-106R-006415
VF 650/60 R 38 NRO	STANDARD	R1W	166 D	DW 23 B	DW 21 B	DW 20 B	650	1745	774	5231	825	TL	E11-106R-005712
VF 650/65 R 38 NRO	STANDARD	R1W	169 D	DW 23 B	DW 21 B	DW 20 B	650	1811	798	5387	875	TL	E11-106R-005022
VF 710/55 R 38	STANDARD	R1W	175 D	DW 25 B	DW 24 B		710	1750	780	5242	825	TL	E11-106R-006844
VF 710/60 R 38 NRO	STANDARD	R1W	171 D	DW 25 B	DW 23 B	DW 23 B	708	1820	794	5447	875	TL	E11-106R-004520
VF 710/70 R 38	STANDARD		181 D	DW 24 B	DW 23 B ; DW 25 B		715	1961	843	5773	925	TL	E11-106R-006163
VF 710/75 R 38	STANDARD	R1W	183 D	DW 24 B	DW 23 B ; DW 25 B		720	2060	905	6151	950	TL	E11-106R-006764
VF 800/70 R 38 CFO	STANDARD		187 D	DW 28 B	DW25 B ; DW27B ; DW30B		804	2085	890	6155	975	TL	E11-106R-007205
VF 900/60 R 38 NRO	STANDARD	R1W	187 D	DW 30 B		DW 27 B	881	2045	882	6053	975	TL	E11-106R-009004
VF 520/85 R 42 CFO	STANDARD	R1W	180 D	DW 18 L			535	1951	876	5841	925	TL	E11-106R-007169
VF 580/85 R 42	SPECIAL	R1W	183	DW20B	DW18B ; MW20B		606	2058	923	6166	975	TL	E11-106R-

CFO			D									006444		
VF 580/85 R 42 CFO	STANDARD	R1W	183 D	DW20B	DW18B ; MW20B		606	2058	923	6166	975	TL	E11-106R-006444	
VF 650/60 R 42	STANDARD		174 D	DW 23 B	DW21B		660	1845	834	5564	875	TL	E11-106R-008774	
VF 650/65 R 42 NRO	STANDARD	R1W	174 D	DW 23 B	DW 21 B		DW 20 B	650	1913	852	5773	925	TL	E11-106R-005713
VF 710/60 R 42 NRO	STANDARD	R1W	173 D	DW 25 B	DW 23 B ; MW 25 B		DW 23 B	710	1930	860	5786	925	TL	E11-106R-002998
VF 710/70 R 42	STANDARD		185 D	DW 25 B	DW 23 B ; DW 24 B			715	2061	921	6182	975	TL	E11-106R-006266
VF 710/70 R 42	STANDARD		193 D	DW 25 B	DW 23 B ; DW 24 B			720	2058	921	6182	975	TL	E11-106R-009053
VF 710/75 R 42	STANDARD	R1W	184 D	DW 24 B	DW 23 B ; DW 25 B			730	2150	937	6412	1000	TL	E11-106R-009074
VF 900/60 R 42 NRO	STANDARD		189 D	DW 30B			DW 28 B	900	2142	937	6390	1025	TL	E11-106R-006165
VF 750/70 R 44	STANDARD	R1W	186 D	DW 25 B	DW 24 B			760	2175	958	6450	1025	TL	E11-106R-006765
VF 520/85 R 46 CFO	STANDARD	R1W	173 D	DW 18 L				535	2052	911	6111	975	TL	E11-106R-008662

Imprimat pe 5/19/2024 10:27 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..