

## AT 625 - Specificații tehnice



### Descriere

LA 625 este potrivită pentru buldoexcavatoare și încărcătoare compacte în toate operațiunile agricole de săpat și încărcare. Banda de rulare extra adâncă asigură rezistență și durabilitate sporite la perforare. AT 625 oferă o tracțiune și stabilitate excelente, precum și o rezistență îmbunătățită la tăiere și așchiere. &nbsp;

### UM

US Standard

### Construcție

 BIAS

### Mașinării

Industrial: Buldoexcavator • Încărcător compact

|                       |           |
|-----------------------|-----------|
| Versiune              | SPECIAL   |
| Tip                   | TT        |
| Dimensiunea anvelopei | 16.9 - 28 |
| LI/SS                 | 152 A8    |

## Dimensiuni US Standard

|                              |          |
|------------------------------|----------|
| Usa code                     | 94055470 |
| Rating de sarcină            | 12       |
| Lățimea secțiunii (inch)     | 17.7     |
| Overall Diameter (inch)      | 55.7     |
| Static Loaded Radius (inch)  | 25.4     |
| Rolling Circumference (inch) | 167.5    |
| Rim Rec                      | DW 15 L  |
| Rim Alt                      | DW 14 L  |
| TRA Code                     | R4       |

## Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 38   |
| 25        | 7850 |

Imprimat pe 5/19/2024 1:59 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..