

AGRIMAX FORCE - Технические спецификации



Description

AGRIMAX FORCE — это радиальные шины премиум-класса от компании BKT, разработанные специально для подготовки почвы, грузоперевозок и уборки урожая на высокомошных тракторах и обеспечивающие максимальные показатели производительности и эффективности. Благодаря технологии IF эти шины при пониженном давлении воздуха способны выдерживать большую нагрузку по сравнению со стандартными шинами. При этом они снижают уплотнение почвы. AGRIMAX FORCE имеет усиленный борт и обеспечивает улучшенную тягу, великолепные способности к самоочищению, снижение расхода топлива и комфортное движение.

UM

International Standard

Construction

 RADIAL

Machinery

Сельское хозяйство: Комбайн • Трактор высокой мощности

Version	STANDARD
Type	TL
Tyre Size	IF 710/60 R 30 CFO
LI/SS	168 D

Dimensions International Standard

Section Width (mm)	708
Overall Diameter (mm)	1614
Static Loaded Radius (mm)	714
Rolling Circumference (mm)	4814
SRI (mm)	775
Rim Rec	DW 25 B
ECE	E4-106R-001407
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2340	2695	3105	3460	3870	4225	4735	5095
from 65 to 40	2575	2965	3415	3805	4255	4645	5205	5600
30	2675	3080	3550	3955	4425	4830	5410	5820
20	2780	3200	3685	4105	4595	5015	5620	6045
10	3270	3765	4335	4830	5400	5895	6610	7110
Upto 30 Cyc	3345	3850	4435	4945	5530	6035	6765	7280
Upto 15 Cyc	3990	4595	5290	5895	6595	7195	8065	8680
Upto 10 Cyc	4375	5040	5805	6465	7230	7895	8845	9520
10 HT	2675	3080	3550	3955	4425	4830	5410	5820

Printed on 19.05.2024 11:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..