

## AGRIMAX V-FLECTO - Технические спецификации



### Description

Шины AGRIMAX V-FLECTO — это ответ компании BKT на потребность в технологиях и характеристиках для высокомоощных тракторов. Эти шины идеально подходят для обработки почвы и грузоперевозок за счет сниженного уплотнения почвы и способности к самоочищению. Благодаря эксклюзивной технологии VF шины AGRIMAX V-FLECTO могут выдерживать большие нагрузки при низком давлении воздуха в них по сравнению со стандартными шинами и шинами с технологией IF. Кроме того, они хорошо зарекомендовали себя при движении на высокой скорости. Эти шины также характеризуются опцией узкого обода, что позволяет устанавливать их на стандартные ободья. Компания BKT разработала эти шины с оптимизированной геометрией для повышения комфорта движения как в поле, так и на дороге с одновременным уменьшением расхода топлива.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Сельское хозяйство: Трактор высокой мощности

Version	STANDARD
Type	TL
Tyre Size	VF 750/70 R 44
LI/SS	186 D

## Dimensions US Standard

Usa code	94066926
Section Width (inch)	29.9
Overall Diameter (inch)	85.6
Static Loaded Radius (inch)	37.7
Rolling Circumference (inch)	253.9
Rim Rec	DW 25 B
Rim Alt	DW 24 B
ECE	E11-106R-006765
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	8960	10200	11820	13350	14870	16390	17920	19060
From 40 to 25	9840	11310	12890	14660	16340	18010	19690	20940
20	10040	11540	13250	14960	16670	18370	20080	21360
12	10240	11770	13510	15260	17000	18740	20480	21780
5	10840	12440	14290	16130	17980	19820	21660	23040
*Upto 5 Cyc with front loader	13790	15840	18190	20520	22870	25220	27570	29320
5 HT	10040	11540	13250	14960	16670	18370	20080	21360

\* \*For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 19.05.2024 6:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..