

EARTHMAX SR 55 - Технические спецификации



Description

EARTHMAX SR 55 — это радиальные шины с цельным металлокордом, которые изготовлены специально для погрузчиков, бульдозеров и низкопрофильных самосвалов, работающих в самых сложных условиях горных разработок и разработок карьеров. Благодаря отличной устойчивости к порезам за счет более глубокого и гладкого рисунка протектора шины EARTHMAX SR 55 помогут обеспечить наивысшую эффективность работы и сократить время простоя. При этом они очень прочные. Операторы также оценят превосходную устойчивость и тягу.

UM

US Standard

Construction

 RADIAL

Machinery

Производство: Бульдозер • Погрузочно-доставочная машина • Погрузчик

| | |
|-----------|------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 29.5 R 29 |
| LI/SS | 218 A2 |

Dimensions US Standard

| | |
|------------------------------|----------------------|
| Usa code | 94040193 |
| Overall Width (inch) | 30.5 |
| Overall Diameter (inch) | 79.1 |
| Static Loaded Radius (inch) | 35.9 |
| Rolling Circumference (inch) | 238.1 |
| Rim Rec | 25.00/3.5 |
| Rim Alt | 24.00/3.5, 26.00/3.5 |
| Star Rating | ** |
| TRA Code | L5S |

Load capacity (lbs)

| mph / psi | 76 | 80 | 83 | 87 | 91 | 94 |
|-----------|-------|-------|-------|-------|-------|-------|
| 5 | 44100 | 45400 | 46700 | 49400 | 50700 | 52000 |

Printed on 19.05.2024 23:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..