

## EARTHMAX SR 45 M - Tekniska specifikationer

### Description

EARTHMAX SR 45 M är ett stålradialdäck för gruvtruckar. EARTHMAX SR 45 M ger optimal dragkraft och är idealiskt för längre transporter.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Stel dumper



|           |                         |
|-----------|-------------------------|
| Version   | HEAT RESISTANT COMPOUND |
| Type      | TL                      |
| Tyre Size | 24.00 R 35              |
| LI/SS     | 209 B                   |

## Dimensions International Standard

|                            |           |
|----------------------------|-----------|
| TKPH                       | 435       |
| Overall Width (mm)         | 664       |
| Overall Diameter (mm)      | 2180      |
| Static Loaded Radius (mm)  | 980       |
| Rolling Circumference (mm) | 6538      |
| Rim Rec                    | 17.00/3.5 |
| Rim Alt                    | --        |
| Star Rating                | **        |
| TRA Code                   | E4        |

## Load capacity (Kg)

| km/h / bar | 5.00  | 5.25  | 5.50  | 5.75  | 6.00  | 6.25  | 6.50  | 6.75  | 7.00  |
|------------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 50         | 14000 | 14500 | 15500 | 16000 | 16500 | 17000 | 17500 | 18000 | 18500 |

Printed on 5/19/2024 5:35 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..