

FL 695 - Tekniska specifikationer



Description

FL 695 har designats specifikt för släpvagnar i byggindustrin och transporttillämpningar inom jordbruksindustrin med ett unikt slitbanemönster i mittblocket. Tack vare sitt starka däckhölje kan FL 695 bära tunga laster och samtidigt bibehålla stabilitet under alla förhållanden. Dess djupa mönster säkerställer optimal självrensning både på vägar och i terrängen. Flera lager med kordkablar i stål förstärker detta mönster mot punkteringar.

UM

US Standard

Construction

 RADIAL

Machinery

Lantbruk: Släpvagn

Industri: Släpvagn

| | |
|--------------------|---------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | 600/60 R 30.5 |
| LI/SS | 179 D |
| LI/SS DRIVE WHEEL | 179 D |
| LI/SS FREE ROLLING | 179 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94073832 |
| Section Width (inch) | 24.1 |
| Overall Diameter (inch) | 58.9 |
| Static Loaded Radius (inch) | 27.3 |
| Rolling Circumference (inch) | 180.6 |
| Rim Rec | AG20.00 |
| ECE | E11-106R-008503 |

Load capacity (lbs)

| mph / psi | 12 | 17 | 23 | 29 | 35 | 41 | 46 | 52 | 58 | 65 | 73 | 80 | 87 |
|-----------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 40 | -- | -- | -- | 7690 | 8880 | 10090 | 11110 | 12140 | 13330 | 14190 | 15030 | 16060 | 17080 |
| 30 | -- | -- | -- | 9310 | 10760 | 12200 | 13450 | 14680 | 16140 | 17170 | 18200 | 19440 | 20680 |
| 25 | -- | 7670 | 9530 | 10460 | 12090 | 13710 | 15110 | 16500 | 18130 | 19290 | 2060 | 21850 | 23240 |
| 20 | 6460 | 8520 | 10580 | 11620 | 13430 | 15230 | 16780 | 18330 | 20130 | 21430 | 22720 | 24260 | 25800 |
| 15 | 6760 | 8920 | 11080 | 12160 | 14040 | 15930 | 17550 | 19170 | 21060 | 22410 | 23760 | 25380 | 26990 |
| 10 | 7050 | 9310 | 11560 | 12700 | 14670 | 16640 | 18330 | 20030 | 22000 | 23410 | 24820 | 26510 | 28200 |
| 5 | 7690 | 10150 | 12610 | 13840 | 15990 | 17280 | 18150 | 19990 | 21840 | 24000 | 27070 | 28910 | 30750 |

Printed on 5/19/2024 6:52 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..