

AGRIMAX FORCE - Teknik Özellikler



Description

BKT'nin lüks ürünü AGRIMAX FORCE, yüksek güçlü traktörler ve biçerdöverlerle toprak işleme, taşıma ve hasat uygulamaları için özel olarak tasarlanmış, üstün performans ve verimlilik sağlayan radyal bir lastiktir. IF teknolojisi sayesinde, bu lastik, standart bir lastiğe kıyasla daha düşük bir şişirme basıncıyla ağır yükler taşıyarak toprak sıkışmasını azaltır. AGRIMAX FORCE, güçlendirilmiş bir damağa sahiptir ve konforlu bir sürüş deneyimine ek olarak gelişmiş çekiş, üstün kendi kendini temizleme özellikleri ve yakıt ekonomisi sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Biçerdöver • Yüksek güçte traktör

Version	STANDARD
Type	TL
Tyre Size	IF 900/60 R 42 CFO
LI/SS	186 D

Dimensions US Standard

Usa code	94022236
Section Width (inch)	36.1
Overall Diameter (inch)	84.5
Static Loaded Radius (inch)	37.4
Rolling Circumference (inch)	252.6
Rim Rec	DW 30 B
Rim Alt	TW 30 B
ECE	E11-106R-006494
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	8760	10100	11620	12950	14480	15820	17710	19060
From 40 to 25	9630	11100	12780	14240	15920	17380	19480	20900
20	10010	11540	13280	14800	16540	18080	20250	21780
12	10390	11980	13790	15380	17180	18770	21030	22620
5	12220	14090	16210	18080	20200	22070	24730	26600
Upto 20 Cyc	12520	14430	16600	18510	20690	22600	25320	27230
Upto 10 Cyc	14920	17200	19800	22070	24670	26940	30180	32460
Upto 5 Cyc	16370	18860	21710	24210	27050	29540	33100	35600
5HT	10010	11540	13280	14800	16540	18080	20250	21780

Printed on 5/19/2024 5:52 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..