

AGRIMAX RT 600 - Teknik Özellikler

Description

AGRIMAX RT 600; çim saha, hasat ve yayma uygulamaları için ideal bir lastiktir. Geniş temas alanı sayesinde AGRIMAX RT 600, arazide mükemmel bir basınç dağılımı sağlayarak çim sahadaki hasarı azaltır ve toprağınızı korur. Yuvarlak omuz teknolojisi, güçlendirilmiş damak ve daha yüksek diş sayısı sayesinde mükemmel sabitleme ve çekiş sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Biçerdöver • Yayıcı • Traktör



Version	STANDARD
Type	TL
Tyre Size	650/65 R 38
LI/SS	157 D/160 A8

Dimensions US Standard

Usa code	94053667
Section Width (inch)	25.4
Overall Diameter (inch)	71.3
Static Loaded Radius (inch)	32.8
Rolling Circumference (inch)	214.3
Rim Rec	DW 20 B
ECE	E11-106R-002990

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
40	5090	6010	6820	7640	8370	9090
30	5360	6320	7180	8040	8800	9560
25	5560	6550	7440	8330	9130	9920
20	5860	6910	7850	8800	9630	10460
5 LT	6830	8050	9150	10250	11220	12190
5 HT	5860	6910	7850	8800	9630	10460

Printed on 5/19/2024 10:28 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..