

## AGRIMAX RT 600 - Teknik Özellikler

### Description

AGRIMAX RT 600; çim saha, hasat ve yayma uygulamaları için ideal bir lastiktir. Geniş temas alanı sayesinde AGRIMAX RT 600, arazide mükemmel bir basınç dağılımı sağlayarak çim sahadaki hasarı azaltır ve toprağınızı korur. Yuvarlak omuz teknolojisi, güçlendirilmiş damak ve daha yüksek diş sayısı sayesinde mükemmel sabitleme ve çekiş sağlar.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Zirai: Biçerdöver • Yayıcı • Traktör



|           |                    |
|-----------|--------------------|
| Version   | STANDARD           |
| Type      | TL                 |
| Tyre Size | IF 680/85 R 32 CFO |
| LI/SS     | 179 D              |

## Dimensions International Standard

|                            |                 |
|----------------------------|-----------------|
| Section Width (mm)         | 682             |
| Overall Diameter (mm)      | 1960            |
| Static Loaded Radius (mm)  | 846             |
| Rolling Circumference (mm) | 5860            |
| SRI (mm)                   | 925             |
| Rim Rec                    | DW23 B          |
| Rim Alt                    | DW21 B          |
| ECE                        | E11-106R-006401 |

## Load capacity (Kg)

| km/h / bar    | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6   | 2.0   | 2.4   |
|---------------|------|------|------|------|------|-------|-------|-------|
| From 65 to 40 | 3640 | 4185 | 4805 | 5425 | 6045 | 6665  | 7285  | 7750  |
| 30            | 3785 | 4350 | 4995 | 5640 | 6285 | 6930  | 7575  | 8060  |
| 20            | 3930 | 4515 | 5185 | 5855 | 6525 | 7195  | 7865  | 8370  |
| 10            | 4620 | 5310 | 6100 | 6885 | 7675 | 8460  | 9250  | 9840  |
| Upto 30 Cyc   | 4730 | 5440 | 6245 | 7050 | 7855 | 8660  | 9470  | 10075 |
| Upto 15 Cyc   | 5640 | 6485 | 7445 | 8405 | 9365 | 10330 | 11290 | 12010 |
| 10 HT         | 3785 | 4350 | 4995 | 5640 | 6285 | 6930  | 7575  | 8060  |

Printed on 5/19/2024 10:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..