

AGRIMAX RT 765M - Teknik Özellikler



Description

BKT 70 serisi bir lastik olan AGRIMAX RT 765M, toprak işleme, arazi ve kara yolu taşımacılığı, üzüm hasadı ve ilaçlama gibi çeşitli ağır hizmet uygulamalarına yönelik son teknoloji traktörler için uygundur. Geniş temas katmanı, tüm yüzeylerde her zaman mümkün olan en iyi çekiş ve konforu sağlar. Bu lastik mükemmel kendi kendini temizleme özellikleri ve daha az toprak sıkışması sağlar. Çelik kuşaklı teknolojiye sahip iki ebat mevcuttur.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: İlaçlama • Traktör • Üzüm hasat makinesi

Version	SPECIAL
Type	TL
Tyre Size	710/70 R 42
LI/SS	176 D/179 A8

Dimensions US Standard

Usa code	94066483
Section Width (inch)	28.2
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	36.3
Rolling Circumference (inch)	243.1
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-006001
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41
40	6730	7830	8930	10020	11120	12210	13470	14250	15650
30	7080	8220	9370	10530	11670	12820	14140	14960	16430
25	7350	8540	9740	10930	12140	13330	14690	15550	17080
20	7750	9010	10260	11530	12790	14040	15490	16390	18000
5 LT	9030	10490	11960	13430	14900	16370	18040	19090	20980
5 HT	7750	9010	10260	11530	12790	14040	15490	16390	18000

Printed on 5/19/2024 6:26 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..