

AGRIMAX TERIS - Teknik Özellikler



Description

Günümüzün yüksek güçlü biçerdöverleri, ekinlere zarar vermeden ağır ekipman ve yükleri destekleyebilen lastikler gerektirir. BKT, veriminizi artırmak için size en yenilikçi radyal lastikleri sunmak için çalışır. AGRIMAX TERIS, tüm karma operasyonlarınız için doğru ortaktır. Mükemmel çekiş özellikleri ve yüksek yük kapasitesi, tüm hasat işlemlerinde en iyi performansı sağlayan temel özellikleridir. Özel yanak koruması ve güçlendirilmiş omuz, zorlu koşullarda ve tarlalarda anız varsa da, direnci artırır; böylece ürün kullanım ömrünü uzatır.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Pamuk Toplama Makinesi • Biçerdöver

Version	STANDARD
Type	TL
Tyre Size	750/65 R 26 CHO (28L R 26)
LI/SS	171 A8/B

Dimensions US Standard

Usa code	94039111
Section Width (inch)	30.1
Overall Diameter (inch)	64.4
Static Loaded Radius (inch)	28.1
Rolling Circumference (inch)	193.2
Rim Rec	DW 25 B
Rim Alt	DW 23 B
ECE	E4-106R-001496

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	6430	7360	9010	9700	10870	11680	12610	13560
25	6430	7360	9010	9700	10870	11680	12610	13560
20	6890	7890	9630	10390	11640	12510	13500	14520
10 Cyc	10600	12150	14850	16000	17930	19280	20810	22380
5 Cyc	11570	13260	16200	17460	19560	21030	22710	24400

Printed on 5/19/2024 4:54 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..