

AGRIMAX TERIS - Teknik Özellikler



Description

Günümüzün yüksek güçlü biçerdöverleri, ekinlere zarar vermeden ağır ekipman ve yükleri destekleyebilen lastikler gerektirir. BKT, veriminizi artırmak için size en yenilikçi radyal lastikleri sunmak için çalışır. AGRIMAX TERIS, tüm karma operasyonlarınız için doğru ortaktır. Mükemmel çekiş özellikleri ve yüksek yük kapasitesi, tüm hasat işlemlerinde en iyi performansı sağlayan temel özellikleridir. Özel yanak koruması ve güçlendirilmiş omuz, zorlu koşullarda ve tarlalarda anız varsa da, direnci artırır; böylece ürün kullanım ömrünü uzatır.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Pamuk Toplama Makinesi • Biçerdöver

Version	STANDARD
Type	TL
Tyre Size	900/60 R 32 CHO
LI/SS	181 A8/178 B

Dimensions International Standard

Section Width (mm)	886
Overall Diameter (mm)	1910
Static Loaded Radius (mm)	854
Rolling Circumference (mm)	5700
SRI (mm)	900
Rim Rec	DW 27 B
Rim Alt	DW 28 B ; DW 30 B
ECE	E4-106R-001431

Load capacity (Kg)

km/h / bar	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	3375	3825	4800	5325	5925	6375	6975	7500
40	3715	4210	5280	5860	6520	7015	7675	8250
30	3975	4505	5655	6270	6980	7510	8215	8830
15 Cyc	6130	6945	8715	9670	10760	11575	12665	13615
10 Cyc	6685	7575	9505	10545	11735	12625	13815	14850

Printed on 5/19/2024 9:50 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..