

AGRIMAX TERIS - Teknik Özellikler



Description

Günümüzün yüksek güçlü biçerdöverleri, ekinlere zarar vermeden ağır ekipman ve yükleri destekleyebilen lastikler gerektirir. BKT, veriminizi artırmak için size en yenilikçi radyal lastikleri sunmak için çalışır. AGRIMAX TERIS, tüm karma operasyonlarınız için doğru ortaktır. Mükemmel çekiş özellikleri ve yüksek yük kapasitesi, tüm hasat işlemlerinde en iyi performansı sağlayan temel özellikleridir. Özel yanak koruması ve güçlendirilmiş omuz, zorlu koşullarda ve tarlalarda anız varsa da, direnci artırır; böylece ürün kullanım ömrünü uzatır.

UM

US Standard

Construction

 RADIAL

Machinery

Zirai: Pamuk Toplama Makinesi • Biçerdöver

Version	STANDARD
Type	TL
Tyre Size	900/60 R 32 CHO
LI/SS	181 A8/178 B

Dimensions US Standard

Usa code	94029723
Section Width (inch)	34.9
Overall Diameter (inch)	75.2
Static Loaded Radius (inch)	33.6
Rolling Circumference (inch)	224.4
Rim Rec	DW 27 B
Rim Alt	DW 28 B ; DW 30 B
ECE	E4-106R-001431

Load capacity (lbs)

mph / psi	12	15	20	23	29	35	41	46
30	7440	8430	10580	11740	13060	14050	15380	16530
25	8190	9280	11640	12920	14370	15460	16920	18190
20	8760	9930	12470	13820	15390	16560	18110	19470
10 Cyc	13510	15310	19210	21320	23720	25520	27920	30010
5 Cyc	14740	16700	20950	23250	25870	27830	30460	32740

Printed on 5/19/2024 4:04 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..