



AGRIMAX TERIS - Veri Sayfasını İndir



Description

Günümüzün yüksek güçlü biçerdöverleri, ekinlere zarar vermeden ağır ekipman ve yükleri destekleyebilen lastikler gerektirir. BKT, veriminizi artırmak için size en yenilikçi radyal lastikleri sunmak için çalışır. AGRIMAX TERIS, tüm karma operasyonlarınız için doğru ortaktır. Mükemmel çekiş özellikleri ve yüksek yük kapasitesi, tüm hasat işlemlerinde en iyi performansı sağlayan temel özellikleridir. Özel yanak koruması ve güçlendirilmiş omuz, zorlu koşullarda ve tarlalarda anız varsa da, direnci artırır; böylece ürün kullanım ömrünü uzatır.

UM

International Standard

Construction

 RADIAL

Machinery

Zirai: Pamuk Toplama Makinesi • Biçerdöver

| SIZE | Version | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|------------------------------------|----------|-----------------|----------------------|---|------|------|-----|------|-----|------|-----------------|
| 620/75 R 26 CHO | STANDARD | 166 A8/B | DW 20 B | | 625 | 1590 | 730 | 4851 | 750 | TL | E4-106R-001419 |
| 750/65 R 26 CHO (28L R 26) | STANDARD | 166 A8/B | DW 25 B | DW 23 B | 764 | 1636 | 713 | 4908 | 750 | TL | E4-106R-000810 |
| 750/65 R 26 CHO (28L R 26) | STANDARD | 171 A8/B | DW 25 B | DW 23 B | 764 | 1636 | 713 | 4908 | 750 | TL | E4-106R-001496 |
| 710/55 R 28 CHO | STANDARD | 164 A8/B | DW 23 B | | 716 | 1493 | 663 | 4442 | 700 | TL | E11-106R-005940 |
| 620/75 R 30 CHO | STANDARD | 168 A8/B | DW 20 B | | 625 | 1692 | 779 | 5169 | 800 | TL | E4-106R-001420 |
| 1050/50 R 32 CHO | STANDARD | 184 A8/181 B | 36.0 VA | | 1059 | 1893 | 840 | 5685 | 875 | TL | E4-106R-000813 |
| 650/75 R 32 CHO | STANDARD | 172 A8/B | DW 21 B | DW 20 B ; DW 23 B | 670 | 1795 | 816 | 5378 | 850 | TL | E4-106R-001425 |
| 800/65 R 32 CHO (30.5L R 32) | STANDARD | 178 A8/175 B | DW 27 B | DW 25 B ; DH 27 B | 818 | 1853 | 838 | 5551 | 875 | TL | E4-106R-001430 |
| 900/60 R 32 CHO | STANDARD | 185 A8/182 B | DW 27 B | DW 28 B ; DW 30 B | 875 | 1910 | 875 | 5775 | 900 | TL | E4-106R-001433 |
| 900/60 R 32 CHO | STANDARD | 181 A8/178 B | DW 27 B | DW 28 B ; DW 30 B | 886 | 1910 | 854 | 5700 | 900 | TL | E4-106R-001431 |
| IF 710/75 R 32 CFO | STANDARD | 183 A8/B | DW 25 B | DW 23 B | 716 | 1879 | 851 | 5653 | 875 | TL | E11-106R-005025 |
| IF 580/80 R 34 CFO | STANDARD | 177 D | DW 20 B ; DW 20 A | DW 21 A ; DW 21 B | 586 | 1792 | 810 | 5422 | 850 | TL | E4-106R-001833 |
| IF 710/75 R 34 CFO | STANDARD | 184 A8/B | DW 25 B | | 716 | 1930 | 870 | 5852 | 900 | TL | E11-106R-004899 |
| 520/85 R 42 | STANDARD | 168 D | DW 16 L | W15L ; DW15L ; DD16L ; W16L ; DD18L ; DW18L ; W18L | 516 | 1951 | 890 | 5851 | 925 | TL | E4-106R-001829 |

Printed on 5/19/2024 7:42 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..