

## AT 625 - Teknik Özellikler



### Description

AT 625 çiftçilik alanındaki tüm kazı ve yükleme faaliyetlerinde ters kepçe yükleyiciler ve kompakt damperli kamyonlarla kullanım için uygundur. Ekstra derin diş deseni, delinmeye karşı artırılmış dayanıklılık ve sağlamlık sunar. AT 625 kusursuz çekiş ve istikrarın yanı sıra kesilme ve parçalanmalara karşı gelişmiş dayanıklılığa sahiptir.

### UM

International Standard

### Construction

BIAS

### Machinery

Endüstriyel: Bekoloder • Küçük yükleyici

|           |            |
|-----------|------------|
| Version   | INDUSTRIAL |
| Type      | TT         |
| Tyre Size | 16.9 - 28  |
| LI/SS     | 152 A8     |

## Dimensions International Standard

|                            |         |
|----------------------------|---------|
| Ply Rating                 | 12      |
| Section Width (mm)         | 450     |
| Overall Diameter (mm)      | 1415    |
| Static Loaded Radius (mm)  | 645     |
| Rolling Circumference (mm) | 4254    |
| Rim Rec                    | DW 15 L |
| Rim Alt                    | DW 14 L |
| TRA Code                   | R4      |

## Load capacity (Kg)

|            |      |
|------------|------|
| km/h / bar | 2.60 |
| 40         | 3550 |

Printed on 5/19/2024 4:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..