

EARTHMAX SR 31 - Teknik Özellikler



Description

EARTHMAX SR 31 Tamamen Çelikten yapılmış radyal lastik belden kırmalı kaya kamyonları ve tekerlekli yükleyiciler için özel olarak tasarlanmıştır. Yönlü olmayan sert blok diş deseni çamurlu zeminde bile mükemmel çekiş ve manevra kabiliyetine imkan verirken çok katlı çelik kuşaklar olağanüstü güç ve denge sağlar. Üstün sürüş konforunun yanı sıra, EARTHMAX SR 31 kesilmeye ve ısıya dirençli özel bir sırt hamuru ile üretilir. Ayrıca, radyal gövde yapısı azalan yuvarlanma direnci sağlayarak önemli ölçüde yakıt tasarrufu sunar.

UM

US Standard

Construction

 RADIAL

Machinery

Endüstriyel: Dozer • Yükleyici

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Dozer • Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	26.5 R 25
LI/SS	193 B/202 A2

Dimensions US Standard

Usa code	94053735
TMPH	158
Overall Width (inch)	27.1
Overall Diameter (inch)	68.6
Static Loaded Radius (inch)	30.2
Rolling Circumference (inch)	204.7
Rim Rec	22.00/3.0
Star Rating	**/*
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	58	62	65	69	73	76
30	20900	21500	22700	23400	24700	25400
5	28300	29100	30900	32000	33100	-

Printed on 5/19/2024 1:38 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..