

EARTHMAX SR 35 - Teknik Özellikler



Description

Earthmax SR 35 özellikle belden kırma damperli kamyonlar ve tekerlekli yükleyiciler için tasarlanmış, alçak profilli, Tamamen Çelikten radyal bir lastiktir. Sıra dışı çekiş ve flotasyon gerektiren faaliyetler için idealdir. Earthmax SR 35 hem kusursuz çekiş, hem de istikrar sağlar. Çelik kuşaklı güçlü gövdesi sayesinde, olağanüstü sağlamlık ve yarılmalara ve kesilmelere karşı dayanıklılık sunar. Lastik, kesilmelere karşı dayanıklı bileşiği ile ağır çalışma koşullarında bile maksimum hizmet ömrü sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Dozer •
Yükleyici

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	775/65 R 29
LI/SS	195 B

Dimensions US Standard

Usa code	94064427
TMPH	151
Overall Width (inch)	30.5
Overall Diameter (inch)	69
Static Loaded Radius (inch)	31
Rolling Circumference (inch)	209.1
Rim Rec	24.00/3.5
Rim Alt	24.00/3.0, 25.00/3.5
Star Rating	**
TRA Code	E3

Load capacity (lbs)

mph / psi	58	62	65	69
30	24000	24700	26000	26800

Printed on 5/19/2024 4:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..