

EARTHMAX SR 35 - Teknik Özellikler



Description

Earthmax SR 35 özellikle belden kırma damperli kamyonlar ve tekerlekli yükleyiciler için tasarlanmış, alçak profilli, Tamamen Çelikten radyal bir lastiktir. Sıra dışı çekiş ve flotasyon gerektiren faaliyetler için idealdir. Earthmax SR 35 hem kusursuz çekiş, hem de istikrar sağlar. Çelik kuşaklı güçlü gövdesi sayesinde, olağanüstü sağlamlık ve yarılmalara ve kesilmelere karşı dayanıklılık sunar. Lastik, kesilmelere karşı dayanıklı bileşiği ile ağır çalışma koşullarında bile maksimum hizmet ömrü sağlar.

UM

US Standard

Construction

 RADIAL

Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Dozer •
Yükleyici

| | |
|-----------|-----------------------------|
| Version | CUT RESISTANT COMPOUND |
| Type | TL |
| Tyre Size | 875/65 R 29 (35/65 R 29) |
| LI/SS | 203 B |

Dimensions US Standard

| | |
|------------------------------|----------------------|
| Usa code | 94059805 |
| TMPH | 191 |
| Overall Width (inch) | 35 |
| Overall Diameter (inch) | 73.2 |
| Static Loaded Radius (inch) | 32.1 |
| Rolling Circumference (inch) | 218.9 |
| Rim Rec | 27.00/3.50 |
| Rim Alt | 27.00/3.0, 28.00/3.5 |
| Star Rating | ** |
| TRA Code | E3 |

Load capacity (lbs)

| mph / psi | 58 | 62 | 65 | 69 |
|-----------|-------|-------|-------|-------|
| 30 | 30900 | 31400 | 33300 | 34200 |

Printed on 5/19/2024 4:19 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..