

EARTHMAX SR 41 - Teknik Özellikler



Description

EARTHMAX SR 41 (E-4 / L-4) Belden Kırmalı Kaya Kamyonları, Yükleyiciler ve Dozerler için mükemmel bir Tamçelik radyal lastiktir. Tamamen çelik yapısı ve özel blok diş deseni sayesinde EARTHMAX SR 41, delinmelere karşı mükemmel direnç ve daha uzun kullanım ömrü sağlar. Lastik, kesintisiz uzun çalışma saatlerine ek olarak olağanüstü konfor sunar. EARTHMAX SR 41, yeraltında taşıma işlemlerinde kullanılan Düşük profilli damperli kamyonlar (LPDT) için E4**** olarak da sunulmaktadır.

UM

International Standard

Construction

 RADIAL

Machinery

Yoldışı: Belden kırmalı kaya kamyonu (ADT) • Dozer • Yükleyici • Düşük profilli damperli kamyon

Version

CUT RESISTANT COMPOUND (UMS)

Type

TL

Tyre Size

26.5 R 25

Dimensions International Standard

Overall Width (mm)	678
Overall Diameter (mm)	1742
Static Loaded Radius (mm)	775
Rolling Circumference (mm)	5150
Rim Rec	22.00/3.0
Star Rating	****
TRA Code	E4

Load capacity (Kg)

Printed on 5/19/2024 12:08 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..